



4000 Series Tamper Proof Outlet

Features & Benefits

- Tamper proof design
- High density, single gang unit
- Available in a 2 or 4 port version
- Enhanced Category 5 performance
- Designed for direct wall mounting
- Custom logo service available

Specifications

Width	87 mm
Depth	27 mm
Height	87 mm
Height (including tamper proof cover)	120 mm
Spacer Plate Depth	8 mm
Material	ABS thermoplastic resin, with grade UL94 VO at 1.5 mm flame retardancy
Finish	High gloss
IDC Blocks	4-way industry standard IDC blocks
IDC Colour	Code IDC colour code to T568B
PCB	1.6 mm double sided PTH boards
Conforms	to ANSI/TIA-568-C Enhanced Category 5 Specification

Ordering Information

Product Description	Part Number
CCS Cat 5e 4 Way Tamper proof Wall Outlet	008-001-012-01
CCS Cat 5e 2 Way Tamper proof Wall Outlet	008-001-012-03

The Connectix 4000 Series offers Enhanced Category 5 performance in a High-Density package.

The Tamper proof outlet restricts the user's access to patch leads, eliminating unauthorised or accidental patch lead disconnection which is one of the most common causes of network problems.

The 4000 Series is extremely quick and easy to install; just attach the base plate, snap in the PCB, punch down the cables and install the cover. But the Tamper proof version has the added benefit that leads cannot be unplugged without first removing the cover, and the position of the sockets allow for a compact installation without protruding leads.

The 4000 Series outlets have been designed for direct wall mounting with top entry mini trunking. In addition, they fit on a standard back box to provide maximum mounting flexibility.

